

# Package: RI2by2 (via r-universe)

September 7, 2024

**Type** Package

**Title** Randomization Inference for Treatment Effects on a Binary Outcome

**Version** 1.4

**Date** 2023-11-07

**Author** Joseph Rigdon <jrigdon@wakehealth.edu>

**Maintainer** Joseph Rigdon <jrigdon@wakehealth.edu>

**Imports** compiler, gtools, Rcpp

**LinkingTo** Rcpp

**Description** Computes attributable effects based confidence interval, permutation test confidence interval, or asymptotic confidence interval for the average treatment effect on a binary outcome. Methods outlined in further detail in Rigdon and Hudgens (2015) <doi:10.1002/sim.6384>.

**License** GPL (>= 3)

**Suggests** testthat

**NeedsCompilation** yes

**Date/Publication** 2023-11-11 11:33:20 UTC

**Repository** <https://joerigdon.r-universe.dev>

**RemoteUrl** <https://github.com/cran/RI2by2>

**RemoteRef** HEAD

**RemoteSha** 8ddd20ddb8cea2d899d562d95e3dd305dab0ae0

## Contents

AE.CI . . . . .	2
Perm.CI . . . . .	3
Perm.CI.RLH . . . . .	4
Robins.CI . . . . .	5
<b>Index</b>	<b>7</b>

---

AE.CI	<i>Attributable effects based confidence interval for a treatment effect on a binary outcome</i>
-------	--

---

**Description**

Computes the attributable effects based confidence interval for the average treatment effect on a binary outcome in an experiment where  $m$  of  $n$  individuals are randomized to treatment by design.

**Usage**

```
AE.CI(data, level)
```

**Arguments**

data	observed 2 by 2 table in matrix form where row 1 is the treatment assignment $Z=1$ and column 1 is the binary outcome $Y=1$
level	significance level of hypothesis tests, i.e., method yields a $100(1-level)\%$ confidence interval

**Details**

The attributable effects based confidence interval from inverting  $n + 2$  hypothesis tests.

**Value**

tau.hat	estimated average treatment effect
lower	lower bound of confidence interval
upper	upper bound of confidence interval

**Author(s)**

Joseph Rigdon <jrigdon@wakehealth.edu>

**References**

Rigdon, J.R. and Hudgens, M.G. (2015). Randomization inference for treatment effects on a binary outcome. *Statistics in Medicine*, 34(6), 924-935.

**Examples**

```
ex = matrix(c(8,2,3,7),2,2,byrow=TRUE)
AE.CI(ex,0.05)
```

---

Perm.CI	<i>Permutation test confidence interval for a treatment effect on a binary outcome</i>
---------	--

---

### Description

Computes permutation-based confidence intervals for the average treatment effect on a binary outcome in an experiment where  $m$  of  $n$  individuals are randomized to treatment by design.

### Usage

```
Perm.CI(data, level, nperm)
```

### Arguments

data	observed 2 by 2 table in matrix form where row 1 is the treatment assignment $Z=1$ and column 1 is the binary outcome $Y=1$
level	significance level of hypothesis tests, i.e., method yields a $100(1-level)\%$ confidence interval
nperm	number of randomizations to perform for each hypothesis test

### Details

The permutation confidence interval results from inverting  $O(n^4)$  hypothesis tests where  $n$  is the total number of observations in the observed 2 by 2 table. For each hypothesis test, if  $\binom{n}{m}$  is less than or equal to nperm,  $\binom{n}{m}$  randomizations are performed, but if  $\binom{n}{m}$  is greater than nperm, a random sample with replacement of nperm randomizations are performed.

### Value

tau.hat	estimated average treatment effect
lower	lower bound of confidence interval
upper	upper bound of confidence interval

### Author(s)

Joseph Rigdon <jrigdon@wakehealth.edu>

### References

Rigdon, J.R. and Hudgens, M.G. (2015). Randomization inference for treatment effects on a binary outcome. *Statistics in Medicine*, 34(6), 924-935.

### Examples

```
ex = matrix(c(8,2,3,7),2,2,byrow=TRUE)
Perm.CI(ex,0.05,100)
```

---

Perm.CI.RLH	<i>Permutation test confidence interval for a treatment effect on a binary outcome</i>
-------------	--

---

### Description

Computes permutation-based confidence intervals for the average treatment effect on a binary outcome in an experiment where  $m$  of  $n$  individuals are randomized to treatment by design. This function is based on the modified approach (RLH) in Rigdon, Loh and Hudgens (forthcoming). The Chiba (2015) and Blaker (2000) intervals are also returned. There is an additional option of specifying the maximum number of hypothesis tests to be carried out.

### Usage

```
Perm.CI.RLH(data, level, verbose=FALSE, total_tests=NA)
```

### Arguments

data	observed 2 by 2 table in matrix form where row 1 is the treatment assignment $Z=1$ and column 1 is the binary outcome $Y=1$
level	significance level of hypothesis tests, i.e., method yields a $100(1-\text{level})\%$ confidence interval
verbose	If TRUE, returns an additional data frame listing all the values of $(n_{11}, n_{10}, n_{01}, n_{00})$ tested, and the corresponding p-values; default = FALSE.
total_tests	maximum number of hypotheses to be tested in total, with a minimum of two for each possible value of $(n_{10} - n_{01})/n$ ; default = NA. By default, all hypotheses are evaluated until the minimum and maximum values of $(n_{10} - n_{01})/n$ with p-values $\geq \text{level}$ (or $\text{level}/2$ for the Chiba intervals) are found.

### Value

A list with the following items:

Chiba	Chiba confidence interval
RLH	RLH confidence interval
Blaker	Blaker confidence interval
tau.hat	estimated average treatment effect
p_values	if verbose=TRUE, a data frame with all the p-values from the hypothesis tests; default=FALSE

### Author(s)

Wen Wei Loh <wen.wei.loh@emory.edu>

## References

- Rigdon, J.R. and Hudgens, M.G. (2015). Randomization inference for treatment effects on a binary outcome. *Statistics in Medicine*, 34(6), 924-935.
- Chiba, Y. (2015). Exact tests for the weak causal null hypothesis on a binary outcome in randomized trials. *Journal of Biometrics & Biostatistics*, 6(244).
- Chiba, Y. (2016). A note on exact confidence interval for causal effects on a binary outcome in randomized trials. *Statistics in Medicine*, 35(10), 1739-1741.
- Blaker, H. (2000). Confidence curves and improved exact confidence intervals for discrete distributions. *Canadian Journal of Statistics*, 28(4), 783-798.
- Rigdon, J.R., Loh W.W. and Hudgens, M.G. (forthcoming). Response to comment on "Randomization inference for treatment effects on a binary outcome."

## Examples

```
ex = matrix(c(11,1,7,21),2,2,byrow=TRUE)
Perm.CI.RLH(ex,0.05)

ex = matrix(c(7,5,1,27),2,2,byrow=TRUE)
Perm.CI.RLH(ex,0.05)
Perm.CI.RLH(ex,0.05, verbose=TRUE)

ex = matrix(c(33,15,11,37),2,2,byrow=TRUE)
Perm.CI.RLH(ex,0.05, total_tests=1000)
Perm.CI.RLH(ex,0.05)
```

---

Robins.CI	<i>Asymptotic confidence interval for a treatment effect on a binary outcome</i>
-----------	--

---

## Description

Computes the Robins (1988) confidence interval for the average treatment effect on a binary outcome in an experiment where  $m$  of  $n$  individuals are randomized to treatment by design.

## Usage

```
Robins.CI(data, level)
```

## Arguments

data	observed 2 by 2 table in matrix form where row 1 is the treatment assignment $Z=1$ and column 1 is the binary outcome $Y=1$
level	significance level of hypothesis tests, i.e., method yields a $100(1-level)\%$ confidence interval

**Details**

The Robins (1988) confidence interval is similar in form to the well known Wald confidence interval for a difference in proportions, but is guaranteed to have smaller width.

**Value**

tau.hat	estimated average treatment effect
lower	lower bound of confidence interval
upper	upper bound of confidence interval

**Author(s)**

Joseph Rigdon <jrigdon@wakehealth.edu>

**References**

Robins, J.M. (1988). Confidence intervals for causal parameters. *Statistics in Medicine*, 7(7), 773-785.

**Examples**

```
#Example 1 from Robins (1988)
ex = matrix(c(40,60,15,85),2,2,byrow=TRUE)
Robins.CI(ex,0.05)
```

# Index

\* **attributable effects**

AE.CI, 2

\* **permutation test**

Perm.CI, 3

\* **randomization inference**

AE.CI, 2

Perm.CI, 3

Robins.CI, 5

AE.CI, 2

Perm.CI, 3

Perm.CI.RLH, 4

Robins.CI, 5